Design Assumptions for Nebraska Base Drawing NE100-30-005 Anti-Vortex Canopy Hood Inlet for 8”, 10”, 12” and 15” Dia. Corrugated Metal Pipe

Revised: 1/03 Replaces: 5001-61

Anti-Vortex Canopy Hood Inlet for 8”, 10”, 12” and 15” Dia. Corrugated Metal Pipe

The pipe gauge is determined by criteria contained in Table 3, FOTG, Pond 378.

Coating requirements criteria is contained in FOTG Pond (378) Standard.

Corrosion control design procedures contained in EFH NB 6-34a-h.

The coating requirements are determined by criteria contained in EFH NB6-34b for corrosion resistance. Installations of this type may cause negative pressures within the pipe so watertightness as outlined in Standard 378, Page 8, is required for all applications, with over 15 ft. of head.

If the PI of the soil in the embankment is less than 15, the inlet area will be armor coated or have a concrete apron.

This structure does not allow drawdown of the permanent pool.

Where a Nebraska Department of Water Resources (DWR) Water Right Permit is required, consult with the Lead Engineer.

Instructions for
Nebraska Base Drawing NE100-30-005
Anti-Vortex Plate and Hood Inlet for 8”, 10”, 12” and 15” Dia. Corrugated Metal Pipe

---

Fill in the following data fields to automatically fill in the necessary data fields on the drawing.

Title block

Title line(s)

Subtitle line

County, State

Sheet number of

Who / When

	Who (initials)	When (MM/DD/YY)
Designed		
Drawn		
Checked		

Enter directly on drawing

Left click on yellow boxes on drawing to mark with X as required.
Left click blue data fields to enter required information.

Clear Form

Click to clear all form fields

Print Drawing

Note: Select page 3 of 3 for drawing only.



DETAIL OF CANOPY INLET

NOTE:
ALL SEAMS CUT, DUE TO FABRICATION IN HELICAL PIPE, SHALL BE WELDED FOR A LENGTH OF 1" FROM THE EDGE OF THE CUT AND TREATED ACCORDING TO SPECIFICATIONS.

WELD SYMBOLS



NOTE:
ALL WELDS AND HEAT AFFECTED AREAS TO BE TREATED IN ACCORDANCE WITH SPECIFICATIONS.
MATERIALS NOT COATED OR GALVANIZED SHALL BE PAINTED ACCORDING TO PAINT SYSTEM "C" OF PAINT SPECIFICATIONS.

REQUIREMENT TABLE

☒ IN BOX INDICATES ANTI-VORTEX CANOPY HOOD INLET REQUIREMENT

___ GA. PLATE AND CANOPY INLET FOR ___ DIA., ___ GA. PIPE AT ___ % GRADE WITH THE FOLLOWING PIPE REQUIREMENTS:

PIPE CLASSIFICATION

TYPE I FULL CIRCULAR CROSS-SECTION FABRICATED WITH:

☐ ANNULAR CORRUGATIONS
☐ CLOSE RIVETED OR ☐ STANDARD RIVETED
☐ HELICAL CORRUGATIONS

CORRUGATION REQUIREMENTS

NOMINAL SIZE (INCH)

☐ 1 1/2 x 1/4 (AVAILABLE ONLY IN HELICALLY CORRUGATED PIPE)
☐ 2 2/3 x 1/2
☐ 3 x 1

COATINGS AND FABRICATION

SEE METAL PIPE REQUIREMENTS AND COUPLING BAND SHEET

NOTE:
THE FOLLOWING DESIGNATIONS FOR PIPE CLASSIFICATIONS, CORRUGATIONS AND COATINGS WHEN REFERRED TO ON THE DRAWINGS ARE IN ACCORDANCE WITH CURRENT ASTM'S:

A760 STANDARD SPECIFICATION FOR CORRUGATED STEEL PIPE, METALLIC-COATED FOR SEWERS AND DRAINS.

A761 STANDARD SPECIFICATION FOR CORRUGATED STEEL STRUCTURAL PLATE, ZINC-COATED, FOR FIELD BOLTED PIPE, PIPE ARCHES, AND ARCHES.

A762 STANDARD SPECIFICATION FOR CORRUGATED STEEL PIPE, POLYMER PRECOATED FOR SEWERS AND DRAINS.

A849 STANDARD SPECIFICATION FOR POST-APPLIED COATINGS, PAVINGS, AND LININGS FOR CORRUGATED STEEL SEWER AND DRAINAGE PIPE.

A885 STANDARD SPECIFICATION FOR STEEL SHEET, ZINC AND ARAMID FIBER COMPOSITE-COATED FOR CORRUGATED STEEL SEWER, CULVERT AND UNDERDRAIN PIPE.

DIMENSIONS FOR CANOPY

PIPE DIA. INCHES	GRADE %	W INCHES	L INCHES	A DEGREES	*h FEET
8	0-5	1 1/2	4 1/4	57	0.93
	6-15	1 5/8	6 3/8	45	1.00
	16-25	2 1/8	8 7/8	33	1.07
	26-32	2 7/8	10 3/8	26	1.13
10	0-5	1 7/8	5 3/8	56	1.17
	6-15	2	8	45	1.25
	16-25	2 3/4	11	33	1.33
	26-32	3 1/2	13	27	1.42
12	0-5	2 1/4	6 1/2	56	1.40
	6-15	2 3/8	9 5/8	45	1.50
	16-25	3 1/4	13 1/4	33	1.60
	26-32	4 1/4	15 5/8	26	1.70
15	0-5	2 7/8	8 1/8	56	1.75
	6-15	3	12	45	1.88
	16-25	4	16 1/2	33	2.00
	26-32	5 1/4	19 1/2	27	2.13

*MINIMUM "h" FOR FULL PIPE FLOW

Date
Designed
Drawn
Checked
Approved

NRCS Natural Resources Conservation Service

File No.

CAD Dwg.
NE100-30-005.dwg

Sheet of

ANTI-VORTEX CANOPY HOOD INLET FOR 8", 10", 12" AND 15" DIA. CORRUGATED METAL PIPE

Nebraska Standard Drawing
NE100-30-005 Revised 1/03 Replaces 5001-61